

Data Sheet

# VIAVI

## OneAdvisor 800

Modular test platform designed for use in the installation and maintenance of fiber, wireless and transport applications.

The VIAVI OneAdvisor 800 is the first test tool designed to address the challenges of a modern network field technician. By rolling all the key test capabilities into one portable tester and combining it with easy-to-use test process and reporting automation, VIAVI has equipped wireline and wireless service providers, equipment manufacturers, system integrators, and contractors to meet the work-speed and test coverage requirements for telecommunication networks buildouts and maintenance.




### Key Features and Benefits

- Extended modularity; dual-bay, detachable or plug-in (via Module carrier) capability that can be combined
- Job Manager for workflow automation for seamless job between all test functions– Enabled by cloud base StrataSync service
- SAA (Smart Access Anywhere) for Remote Access and coaching

### Measurements

- RF Spectrum Analyzer and Signal Analyzer for 4G and 5G
- Singlemode and multimode OTDR
- CWDM and DWDM OTDR
- Bi-directional Optical Loss and ORL Test
- Optical spectrum analyzer
- CWDM and DWDM optical channel checker
- Broadband optical Power level
- Connector end face inspection
- Ethernet and protocol testing
- Optical dispersion and Attenuation profile
- RF power sensor
- Cable and Antenna Analyzer



## General Information

Inputs and Outputs	
USB	2x USB 2.0 Host
Memory Card	1x micro SD
LAN	RJ-45, 1000 Base-T
Audio	Built-in speaker 1x USB-C for Audio output
Display	8", 1280 x 800 resolution
Power	
Connector	Rectangular DC Jack
External DC Input	19 VDC
Power consumption	Mainframe: 10.8W (w/ 70% brightness setting)
Battery	
Type	14.4 V, 6800 mAh (Lithium ion)
Operating time	MF (mainframe) only: > 8hrs
Charging time	100 % charging
	Standard (one battery): > 2:2 hrs
	Up to 80 % charging Standard (one battery): > 1:40 hrs
Charging temperature	0 to 45°C (32 to 113°F) ≤ 85% RH
Discharging temperature	-20 to 55°C (-4 to 131°F) ≤ 85% RH
Storage temperature	-20 to 60°C (-4 to 140°F)
Operating Temperature	
0 to 40°C (32 to 104°F)	AC Power condition
-10 to 55°C (14 to 131°F)	Battery operation condition
Storage temperature	
-20 to 60 °C (-4 to 140 °F)	
Maximum humidity	
95% RH (noncondensing)	
Memory	
Internal	6.2 GB total, shared by system memory
External	Micro-SD: up to 32GB USB flash memory: limited by size of the flash drive Supported file system: FAT, FAT3, ext4

Environmental	
Shock and Vibration	MIL-PRF-28800F
Bench handling	MIL-PRF-28800F
Drop	MIL-PRF-28800F ETSI EN 300 029-2-7
EMC	IEC/EN 61326-1 FCC part 15B ICES-003

Size and weight (Mainframe)	
Weight	2.0 kg (4.4 lb) without module (including battery)
Size (W x H x D)	270 x 170 x 60 mm (10.6 x 6.7 x 2.3 in) without module

Size and weight (Fiber module receptacle)	
Weight	0.8 kg (1.7 lb) without test module
Size (W x H x D)	270 x 170 x 50 mm (10.6 x 6.7 x 2 in)

Warranty	
3 years*	

\* Applied to Mainframe and module only. For every accessory, 1-year warrant is applied.

## Built-In hardware option

### ONA-PMVFL


Power Meter	
Power Level	+10 to - 60 dBm
Calibrated wavelength	850, 1310, 1550nm
Connector type	Universal push/pull (UPP)
Visual Fault Locator	
Wavelength	650 nm +/- 15nm
Output power level	< 1mW
Laser safety	Class 2 laser

## Platform Ordering Information

Part	Description
ONA-800A*	OneAdvisor ONA-800A Mainframe with Display
<b>Solution Hardware Modules</b>	
E81FMC1	Fiber module receptacle for E8100-series fiber modules
<b>Software Options for OneAdvisor Platform</b>	
ONA-MF-BT	Bluetooth connectivity
ONA-MF-WIFI	WiFi connectivity
SAA-ADVISOR	Smart Access Anywhere for CellAdvisor Products
<b>Accessories for OneAdvisor Platform</b>	
CC-034601	Large Carrying Case for HST and OneExpert
FBP-SD101	Kit FBP-P5000I Digital Probe FiberChekPro SW Case And Tips
FIT-FC-KIT3	Kit FiberChek Autofocus WiFi Microscope Tips for LC/PC SC/PC and SC/APC Case
G700050125	120 watts DC to DC car cigarette lighter charger adapter
G700050127	OneAdvisor 800 AC/DC Power Adapter 160 W 19 V
G700050150	98 Wh Lithium-ion battery
G700050701	OneAdvisor 800 with RA/SPA module hard carrying case with wheels
G710550324	External Battery Charger
JD70050342	Hard Carrying Case With Wheels
JD731B	Directional Power Sensor Average Peak Pulse
JD736B	Terminating Power Sensor_Dual_Average/Peak_Power 20 to 3800 MHz
MP-60A	USB Optical Power Meter with Accessories
ONA-800A-BC	OneAdvisor back cover
ONA-800A-HN	OneAdvisor Harness
ONA-800-DISPL	OneAdvisor Display
ONA-PMVFL	Power Meter and VFL Mainframe Module for OneAdvisor 800

## Managing your workforce, tasks and test data

Test Process Automation (TPA) allows your team to deliver expert-level test results and close projects on the first try, every time. TPA is a closed loop test system that optimizes workflows, eliminates manual, error prone work and automates immediate data reporting for job close out, team progress updates and network health analytics. Execute jobs efficiently to ensure high quality network builds, rapid turn-up/activation, and enhanced operational visibility.



## VIAVI Care Support Plans

### Increase your productivity for up to 5 years with optional VIAVI Care Support Plans:

- Maximize your time with on-demand training, priority technical application support and rapid service.
- Maintain your equipment for peak performance at a low, predictable cost.

Plan availability depends on product and region. Not all plans are available for each product or in every region. To find out which VIAVI Care Support Plan options are available for this product in your region, contact your local representative or visit: [viavisolutions.com/viavicareplan](https://viavisolutions.com/viavicareplan)

## Features

\*5-year plans only

Plan	Objective	Technical Assistance	Factory Repair	Priority Service	Self-paced Training	5 Year Battery and Bag Coverage	Factory Calibration	Accessory Coverage	Express Loaner
 BronzeCare	Technician Efficiency	Premium	✓	✓	✓				
 SilverCare	Maintenance & Measurement Accuracy	Premium	✓	✓	✓	✓*	✓		
 MaxCare	High Availability	Premium	✓	✓	✓	✓*	✓	✓	✓



Contact Us **+1 844 GO VIAVI**  
(+1 844 468 4284)

To reach the VIAVI office nearest you,  
visit [viavisolutions.com/contact](https://viavisolutions.com/contact)

© 2022 VIAVI Solutions Inc.  
Product specifications and descriptions in this document are subject to change without notice.  
Patented as described at  
[viavisolutions.com/patents](https://viavisolutions.com/patents)  
ona800-ds-xpf-nse-ae  
30191107 906 0222